



NOTES:

1. METAL SHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL
 - PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
4. FRAME: STEEL; NICKEL PLATED
5. FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
6. RIVETED INSERTS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
7. COLLARS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
8. CONNECTOR IS PART MARKED: DSS1XPM□B01X CONEC ABC (see note 3)

Directive 2002/95/EC RoHS compliant

| | | | | | | |
|--|-------------|------------|-------|----------------|--------------|--|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND | | | | tolerance | | scale: 2:1 (5:1) |
| | | | | dim. in mm | | material: SEE NOTES |
| | | | | date | name | title: |
| | | | | drawn 10.04.06 | Lehmenlühler | D-SUB MALE 9pos. SOLDER CUP with frame and float mount |
| | | | | appd. 11.04.06 | Mickenbecker | |
| | | | norm | | dwg no: | |
| 2 x c | Ä5047 | 14.01.2014 | Lehm. | d-old | | DIN-A3 |
| 4 x b | Ä4772 | 03.06.2013 | K.H. | | | sh: 1 |
| a | Original | | | | | |
| rev. | description | date | name | | | part no: DSS1XPM□B01X (see note 3) |