

SPECIFICATIONS

FUNCTION:  
2P1T OFF-(ON), LOCK-ON

RATINGS:  
ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E194579):  
17A 125VAC [cUrus]  
12A 250VAC [cUrus]

ELECTRICAL LIFE:  
6,000 Cycles [cUrus]

TEMPERATURE:  
Operating: 0°C to 65°C [cUrus]

APPROVALS:




COLORS

BODY:  
White

ACTUATOR:  
Black

LOCK:  
Black

SCHEMATIC



REV.	A	10/09/23	CAB
COLORS	A	10/09/23	CAB
SPECIFICATIONS	B	11/09/11	BMA
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

REV.	B	2019	11/09/19	BMA
DESCRIPTION	FOR	DATE	DRAWN BY	

CORRECT NOTES

INCHES [MILLIMETERS]	±0.008 [±0.2] / ±1'
GENERAL TOLERANCES	
SCALE	DRAWING NOT TO SCALE

PROJECTION

HY37-6E6-011-0211

DATE: SEPTEMBER 29, 2010

REVISION: B