


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

Loc		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
B		ECO 06 000585		07AUG06	BSV	MZ	



SPECIFICATIONS:

MATERIALS:

CASE: HIGH TEMPERATURE POLYESTER  
 ACTUATOR BUTTON: POLYAMIDE, COLOR: SEE CHART BELOW  
 MOVING CONTACT: COPPER ALLOY, GOLD OVER NICKEL PLATE  
 FIXED CONTACT/TERMINAL: COPPER ALLOY, TIN/LEAD PLATE  
 TERMINAL SEAL: EPOXY

ELECTRICAL:

CONTACT RATING: 0.4 VA MAX. @20 VDC OR PEAK AC  
 INITIAL CONTACT RESISTANCE: 20 MILLIOHMS MAX.  
 INSULATION RESISTANCE: 1000 MEGOHMS @ 500 VDC MIN.  
 DIELECTRIC STRENGTH: 1000 VOLTS RMS @ SEA LEVEL  
 LIFE EXPECTANCY: 80,000 CYCLES

MECHANICAL:


ACTUATION FORCE: 26Kg.  
 ACTUATION TRAVEL: .030"

ENVIRONMENTAL:

OPERATING TEMPERATURE: -22°F TO +149°F (-30°C TO +65°C)  
 STORAGE TEMPERATURE: -22°F TO +149°F (-30°C TO +65°C)

NOTES:

- INTERPRET DRAWING PER ASME Y14.5M-1982



RECOMMENDED HOLE LAYOUT  
 TOLERANCE  $\pm 0.05$  UNLESS  
 OTHERWISE NOTED

(*)	ACTUATOR BUTTON COLOR
(0)	BLACK
(2)	RED
(6)	BLUE

AUGAT D/N 40295-SD

B TO C (MOM.)	B TO A	2XSPDT MOMENTARY	TP21FFG-RA (*)
A TO C	NONE	2XSPST NORMALLY OPEN	TP21CCG-RA (*)
DEPRESSED BUTTON	FREE BUTTON	ACTION	
CONTACTS		MODEL NO.	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. KIRCORIAN	30SEP96	Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK -	APVD -	NAME	
	0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .010 4 PLC ± - ANGLES ± -	PRODUCT SPEC -	APPLICATION SPEC -	PUSH BUTTON SWITCH RIGHT ANGLE, 2 x SINGLE POLE (TPA21**GRA* SERIES)	
MATERIAL SEE SPECIFICATIONS	FINISH SEE SPECIFICATIONS	WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C=4-1437571-1
CUSTOMER DRAWING			SCALE 4:1	SHEET 1 OF 1	REV B

4-1437571-1

A