



Part Number: 8521

Hook-Up/ Lead Wire (Type MW) MIL-W-76C-PVC, (1) 16 AWG (26x30) TC, PVC

[Request Sample](#)

Product Description

One 16 AWG stranded (26x30) tinned copper, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
16	26x30	TC - Tinned Copper	1

Conductor Count:	1
Conductor Size:	16 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.098 in	0.019 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.098 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
3.75 Ohm/1000ft

Shielding:	Unshielded
------------	------------

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	Single conductor in free air @ 30C ambient 22 A

Voltage

Description	Voltage Rating [V]
Mil-W-76C	1000 V RMS Mil-W-76C

Temperature Range

Operating Temp Range:	-40°C To +80°C
-----------------------	----------------

Mechanical Characteristics

Bulk Cable Weight:	12 lbs/1000ft
--------------------	---------------

Standards

UL AWM Style:	N/A
Military Specification:	MIL-W-76C type MWP

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
--------------------------------	-----

EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A
--------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
8521 010100	Black	
8521 0101000	Black	P
8521 013100	Blue, Dark	
8521 0131000	Blue, Dark	P
8521 006100	Blue, Light	
8521 0061000	Blue, Light	P
8521 001100	Brown	
8521 0011000	Brown	P
8521 008100	Gray	
8521 0081000	Gray	P
8521 005100	Green, Dark	
8521 0051000	Green, Dark	P
8521 003100	Orange	
8521 0031000	Orange	P
8521 012100	Pink	
8521 002100	Red	
8521 0021000	Red	P
8521 011100	Tan	
8521 0111000	Tan	P
8521 007100	Violet	
8521 0071000	Violet	P
8521 009100	White	
8521 0091000	White	P
8521 0141000	White, Black Stripe	A
8521 018100	White, Blue Stripe	A
8521 0181000	White, Blue Stripe	A
8521 0191000	White, Brown Stripe	A
8521 0211000	White, Gray Stripe	
8521 0161000	White, Green Stripe	A
8521 0201000	White, Orange Stripe	A
8521 0151000	White, Red Stripe	A
8521 0221000	White, Violet Stripe	A
8521 0171000	White, Yellow Stripe	A
8521 004100	Yellow	
8521 0041000	Yellow	P

Footnote:	A - STOCKED STRIPE COLORS.
Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.