INACTIVE 11/8/77
REFER TO I.S.-7046

SYMBOL B SYMBOL A

WIRE CRIMP				TERMINAL CRIMP HEIGHT
CRIMP SYMBOL	DIM	GO	NO GO	
A	F	.0446	.0488	.0510 / .0470
	D	.0528	.0562	
B	F	.0509	.0549	.0590 / .0540
	D	.0598	.0632	



SYMBOL A SYMBOL B

INSULATION CRIMP			
CRIMP SYMBOL	DIM	GO	NO GO
A	F	.0909	.1089
	D	.1129	.1273
B	F	.0909	.1089
	D	.1129	.1273

SEE NOTE "5"

INACTIVE,
REFER TO
IS SHEET 7046
11/8/77





INSULATION CRIMP
CRIMP SYMBOL A&B



WIRE CRIMP
CRIMP SYMBOL B

ENLARGED END VIEW OF GAGE



WIRE CRIMP
CRIMP SYMBOL A



SIDE VIEW OF GAGE



DOUBLE END HANDLE AGD STD

APPLICATION TOOLING ENGRG.
CONNECTOR PRODUCTS DIV.

SUGGESTED GAGE DESIGN

	1-MA	300449	PIN-RETAINING	4
	2 —	21045-6	RING-RETAINING	3
	2-MA	300432	PIN-RETAINING	2
	4 —	21045-3	RING-RETAINING	1
DWG SIZE	NUMBER	NAME	REMARKS	ITEM NO

INACTIVE

1. CRIMP GAGE DIMENSIONS APPLY WHEN TOOL IS CLOSED OR BOTTOMED BUT NOT UNDER PRESSURE.
2. FOR REPLACEMENT OF PARTS OTHER THAN PINS AND SNAP RINGS, TOOL IS TO BE RETURNED TO AMP INC. HARRISBURG, PENNA. TO INSURE PROPER CERTI-CRIMP ADJUSTMENT.
3. FOR TOOL USAGE SEE INSTRUCTION SHEET No 7046
4. HAND TO CAN BE CHECKED BY MEASURING TERMINAL CRIMP HEIGHT
5. GAGE DIMENSIONS ARE MEASURED WITH INSULATION ADJUSTMENT PINS IN "1 POSITION

LTR	REVISION RECORD	DR	CHK	DATE
A	INACTIVE PER ECN HT-1113	S-I	[illegible]	5/8/73

NUMBER C-90088

REQUIRED PER ASSEMBLY

DESCRIPTION

©1963 BY AMP INCORPORATED. ALL RIGHTS RESERVED.
AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.

CUSTOMER COPY
REFERENCE ONLY

DR E.L. Hauk 6/14/63
CHK L.S. Smith 6/25/63
DE [illegible] 6/25/63
APP J.R. Lingg 6-25-63

MATERIAL AND FINISH

WIRE — RANGE — INSULATION

~~TOLERANCE EXCEPT AS NOTED~~ .X ±.015 .XX ±.010 .XXX ±.005 ANGLES ±1°-0'

SCALE

AMP INCORPORATED
HARRISBURG, PENNA.

CLASS

TYPE

LOC R B NO C-90088 REV A

NAME DOUBLE ACTION HAND TOOL

PRINT 55

DIMENSIONS IN INCHES DO NOT SCALE PRINT

AMP 1253 REV 7/68