

FO connectors - FOC-C-SCRJ-GOF-SM-PC/10 - 1411301

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



SC-RJ connector, with long bend protection, for single mode 9/125 μm , PC polishing, blue, value pack: 10 pcs

Product Description

SC-RJ connector, for wires 2.0 - 3.0 mm in diameter, single mode 9/125 μm , PC polishing

The reusable connector is particularly suitable for quick and easy field connection, as there is no need for bonding and polishing.

Value pack: 10 pcs.

Why buy this product

- suitable for quick and easy field assembly or repair
- No bonding or polishing
- Reusable connectors
- A real alternative to splicing
- Optimum attenuation values with easy assembly
- Long-term durability, thanks to the latest index matching gel
- the 8° fiber transition ensures optimum return loss (RL)
- meets IEC 61754-4 (SC) and FprEN 50377-17-1 (connectors for field assembly)
- Cleave technology
- Reusable connectors

Key Commercial Data

| | |
|----------------------|----------|
| Packing unit | 1 STK |
| Custom tariff number | 85367000 |
| Country of origin | Bulgaria |

Technical data

Mechanical characteristics

| | |
|-----------------------------|---|
| Locking type | Clip locking |
| Fiber type | Quartz fiber |
| Fiber | 9/125 μm |
| Ferrule diameter | 2.50 mm |
| Insertion/withdrawal cycles | ≥ 500 (according to IEC 61300-2-2) |

FO connectors - FOC-C-SCRJ-GOF-SM-PC/10 - 1411301

Technical data

Mechanical characteristics

| | |
|---------------------|--|
| Connection method | mechanical splice |
| Type of contact | Index matching gel with extended temperature range |
| Max. cable diameter | 2 mm ... 3 mm |
| Cable exit | straight |
| Type of cable | For all common cable types |
| Cable structure | Semi-loose compact wires (STB) |
| Color | blue |
| Wire diameter | 2 mm ... 3 mm |

Ambient conditions

| | |
|---------------------------------|--------------------------------|
| Ambient temperature (operation) | -10 °C ... 60 °C (IEC 61300-2) |
| Degree of protection | IP20 |

Material data

| | |
|--|-------------------|
| Flammability rating according to UL 94 | V0 |
| Ferrule material | Zirconia ceramics |

Line characteristics

| | |
|---------------------------------------|--|
| Type of cable | For all common cable types |
| Cable type | Fiberglass |
| Cable structure | Semi-loose compact wires (STB) |
| Number of fibers | 1 |
| Fiber type | Single-mode fiberglass |
| Fiber | GOF |
| Attenuation | ≤ 0.5 dB ((95%) according to IEC 61300-3-34) |
| | ≤ 0.2 dB ((typical value) according to IEC 61300-3-34) |
| Tensile strength short-term/long-term | 70N (120s.) bei Aderdurchmesser >2 mm |
| cable layer type | Indoors |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27180802 |
| eCl@ss 8.0 | 19170122 |
| eCl@ss 9.0 | 19170122 |

FO connectors - FOC-C-SCRJ-GOF-SM-PC/10 - 1411301

Classifications

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001122 |
|----------|----------|

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

| |
|-----|
| EAC |
|-----|

Accessories

Accessories

Assembly tool

FO accessories - FOC-TOOL-FERRULECLEANER-2.50 - 1407029



2.50 mm ferrule cleaner, for ST, SC, FC, E2000 (also APC), approx. 500 cleaning cycles

Tool set

Tool set - FOC-TOOL-GOF KONF SET - 1411049



Tool set for GOF assembly

FO connectors - FOC-C-SCRJ-GOF-SM-PC/10 - 1411301

Accessories

Necessary add-on products

Tool set - FOC-TOOL-GOF KONF SET - 1411049



Tool set for GOF assembly
