

## Specification Sheet

Part Number: T50L1C2



Standard Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Brown, 100/pkg

Article Number	111-05443
Type	T50L
Color	Brown (BN)
Features & Benefits	<ul style="list-style-type: none"><li>• Inside serrations allow for strong hold on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
Quantity Per	bag

### Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Standard Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Brown, 100/pkg
<b>Global Part Name</b>	T50L-PA66-BN
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	15.35
<b>Length L (Metric)</b>	390.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.19
<b>Width W (Metric)</b>	4.8
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	4.3
<b>Bundle Diameter Max (Metric)</b>	109.2

**Thickness T (Metric)**

1.4

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**US MIL SPEC**

SAE-AS33671

MS3367-2-1

**Flammability**

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**Certification/Specification WEB**

UL-ZODZ.E64139 CAGE Code 53421

**UL Recognized (US)**

Yes

**UL Listed (US and Canada)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

100

**Customs Number**

3926909987

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)