


Star-delta TIMER


Order Code

H3CR-G8EL AC200-240


Dimensions (Unit: mm)



Front



Top view




Side view

There is a case that the marks of Approval are updated.

Pin Connection

H3CR-G8EL (Contact Output)




Note: Leave terminal 4 open.

Technical criteria

Rated supply voltage	200 to 240 VAC (50/60 Hz)
Reset Power Off time	0.5 s min
Operating Temperature	-10 to 55 °C
Signal Input type	—
Start Signal input time	—
Output	Contact Output: Time limit contact, SPST-NO (Star-operation), SPST-NO (Delta-operation) Instantaneous contact, SPST-NO 5 A at 250 VAC/30 VDC, 0.15 A at 125 VDC, resistive load (cosφ = 1) Minimum applicable load: 10 mA at 5 VDC (failure level: P). Contact Material: Ag alloy
Accuracy of Star-delta transfer time	±25% Full Scale + 5 ms or less
Operating mode	Star-delta timer with instantaneous output
Safety Standards	UL 508, CSA C22.2 No.14 CCC CE Marking under EN 61812-1, IEC 60664-1 Marine Approvals (NK, Lloyds)

For the most recent information on models that have been certified for safety standards, refer to your OMRON website.

Nomenclature




Time range

Time unit Scale number (max.)	Star operation time ranges	
6	Set time range	0.5 to 6 s
12		1 to 12 s
60		5 to 60 s
120		10 to 120 s

Star-delta transfer time	Programmable at 0.05 s, 0.1 s, 0.25 s, 0.5 s, 0.75 s, or 1.0 s
---------------------------------	--

Timing Chart



t1: Star operation time setting
t2: Star-delta transfer time

Accessories

DIN rail Mount Socket P2CF-08-E/P2CF-11-E	On-panel Mount Socket P3G-08/P3GA-11	On-panel Mounting Adaptor Y92F-30	Hard protect Cover Y92A-48B	Water Proof Cover (IP66) Y92A-48N
---	--	---	---	---

OMRON Corporation Industrial Automation Company
Kyoto, JAPAN

Contact: www.ia.omron.com

Regional Headquarters

OMRON EUROPE B.V.

Wegalaan 67-69, 2132 JD Hoofddorp
The Netherlands
Tel: (31) 2356-81-300/Fax: (31) 2356-81-388
<https://industrial.omron.eu/en/home>

OMRON ELECTRONICS

Burhaniye Mah. Tunuslu Mahmut Paşa Cad. No:10
34676 Üsküdar, İstanbul
Tel: (90) 216-556-5130/Fax: (90) 216-556-5160
<https://industrial.omron.com.tr>

© OMRON Corporation 2018 All Rights Reserved.
In the interest of product improvement,
specifications are subject to change without notice.

Cat. No. L154-E1-01

0318 (0318)