

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case that the application demands a high level of reliability, such as automotive,  
 please contact a company representative for further information.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85°C	STORAGE TEMPERATURE RANGE	- °C TO - °C
	VOLTAGE	- V	OPERATING HUMIDITY RANGE	- % TO - %
	CURRENT	- A	APPLICABLE CABLE	DIAMETER MAX φ9.3
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
MECHANICAL CHARACTERISTICS				
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.76 mm, - m/s <sup>2</sup> AT 2 h, FOR 3 DIRECTIONS.	NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	X	-
SHOCK	490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	-
ENVIRONMENTAL CHARACTERISTICS				
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.	X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0				
REMARK		APPROVED	HO.MIWA	06.06.29
		CHECKED	YH.ENAMI	06.06.29
		DESIGNED	TU.TANIGUCHI	06.06.29
		DRAWN	YK.SATO	06.06.28
Unless otherwise specified, refer to JIS C 5402.				
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-040392-02	
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DX30M-68-CV	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL230-5056-0-00	1/