

1

2

3

4

5

6

7

A

A

B

B

C

C

D

D

E

E

F




F

G

G

H

H



Material

- ①Clamp: Brass,Ni plated
- ②Terminal screw: Steel Zinc plating "-" slot type
- ③Wire guard solder pin: Brass,Tin plated
- ④Terminal housing: Thermoplastic (UL94V-0) , GREY

Electrical cULus

Voltage rating: 600V
 Current rating: 65A
 Wire range:
 Solid wire(AWG): 6-22
 Stranded wire(AWG): 6-22
 Torque(Lb-In): 8.7Lb-In
 Screw: M4
 Wire strip length: 6-7mm
 Withstanding Voltage: 2.2KV
 Operating temperature: -40°C to +115°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval: cULus

RoHS compliant



File No.: E349947

Scale	1:1					Date	Name	Customer-No.
TOLERANCE								
X.	±0.50					Drawn	16.12.2010	Schulz
X.X	±0.30					Approved	16.12.2010	Gerber
X.XX	±0.10							
DIM TOL								
X.°	±1°	①	UL Update	23.03.2017	C.Bakula			
		②	Drawn	16.12.2010	Schulz			
Angle	TOL	Id.	Modification	Date	Name	Replace	ASS 4115A CO	rev01
							Sheet	

1

2

3

4

5

6

7