


RECOMMENDED PANEL LAYOUT

| SWITCH FUNCTION | | CONNECTED TERMINAL # | | |
|-----------------|--------|----------------------|--------|--------|
| POS. 1 | POS. 2 | POS. 3 | POS. 4 | POS. 5 |
| 6-7 | 7-8 | B-1 | NONE | 1-3 |

CIRCUIT: SP (45°/45°/90° INDEXING)

CONTACT CONFIGURATION



LEGEND

- =Detent Positions (45° or 90°)
- ⊙ =Key pull possible in these positions

NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
- TERM. NOS. FOR REF. ONLY
- CONTACT RATING: 4A @125VAC/28VDC, 2A @250VAC
- DIELECTRIC STRENGTH: 1KV RMS min. at sea level
- ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.
- MATERIALS:

CONTACTS: Silver Plated Cu (Q Contact material)
 TERMINALS: Gold Plated Cu (Q Contact material)
 MOUNTING NUT: Nickel Plated zinc alloy
 CONTACT SPRING: Piano Wire
 KEYS (2): Brass with code no. A126
 LOCK: Bright Ni plated zinc alloy with Ni facing
 TUMBLER Mechanism: 4-disc tumbler cylinder.

| REV. | ECN No. | DESCRIPTION | DATE | CHKD | AR |
|------|---------|-------------------------|---------|------|----|
| A | 13055 | RELEASED FOR PRODUCTION | 4/17/03 | | AR |

| TITLE | | SCALE | DATE | DR | DWG | REV |
|-------------|--|-------|---------|----|---------|-----|
| K0130V-A126 | | 1:1 | 4/17/03 | AR | K200231 | A |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

