



NOTES

- MATERIALS:**
INSULATOR: GLASS FILLED LCP, 94V-0, COLOR BLACK.
SHIELD: DEEP DRAW STEEL, .020" THICK.
- PLATING: 100 MICRO-INCHES MINIMUM BRIGHT NICKEL OVER COPPER UNDERPLATE OVERALL.
- CONFORMS TO PRODUCT SPECIFICATION PS-71626.
- CONFORMS TO APPLICATION SPECIFICATION PS-71624.
- INSERT MOLDED CONTACT STRIPS ARE SUPPLIED SEPARATELY, SEE SALES DRAWING* SDA-70984-4*** FOR ORDER NUMBERS.
- BULK PACKAGING: 100 SUB-ASSEMBLIES PER CARTON

71624-3001	WITH M-3 THREADED INSERT
71624-3000	WITHOUT M-3 THREADED INSERT
ITEM NUMBER	DESCRIPTION

REVISION NOTE 2 EC NO: UCP2016-0871 DRW: SVANG01 2015/08/26 CHK: DMORGAN 2015/08/26 APPR: SMILLER 2015/09/10	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
	▽=0	mm INCH	IN/MM	4:1	INCH	
	▽=0	4 PLACES ± --- ± ---	DRAWN BY DATE			TITLE
	▽=0	3 PLACES ± --- ± ---	SVANG01 2015/08/26			160 CKT LFH I/O PLUG HSG/SHLD SUB. ASSY. FOR CABLE APPLICATION
	2 PLACES ± --- ± ---	CHECKED BY DATE				molex DOCUMENT NO. SDA-71624-3000 SHEET NO. 1 OF 1
	1 PLACE ± --- ± ---	DMORGAN 2015/08/26				
	0 PLACE ± --- ± ---	APPROVED BY DATE				
		SMILLER 2015/09/10				
		MATERIAL NO.				
		ANGULAR ±1/2°				
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				
		SIZE				