

## Specification Sheet

Part Number: MB19M4



Cable Tie Anchor Mount, .50" x .312", .13" Hole Dia, .1" Max Tie Width, PA66, Natural, 100/pkg

<b>Article Number</b>	151-00294
<b>Type</b>	MB1
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• For use with 18 through 50 pound cable ties to provide stability when securing bundles.</li><li>• Low profile design offers use in space constrained areas.</li><li>• Secures with a single screw providing quick installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton cable tie screw mounts are used with 18 through 50 pound cable ties to provide stability when securing bundles. The low profile design allows for use in space constrained areas. The mounts are installed quick and easy by securing a single screw.
<b>Short Description</b>	Cable Tie Anchor Mount, .50" x .312", .13" Hole Dia, .1" Max Tie Width, PA66, Natural, 100/pkg

**Global Part Name**

MB1-PA66-NA

**Length L (Imperial)**

0.5

**Length L (Metric)**

12.7

**Fixation Method**

Screw Mounting and Rivet

**Width W (Imperial)**

0.312

**Width W (Metric)**

7.92

**Cable Ties**

T18

**Height H (Imperial)**

.13

**Height H (Metric)**

3.30

**Cable Tie Width Max (Imperial)**

0.1

**Cable Tie Width Max (Metric)**

2.54

**Mounting Hole Diameter D (Imperial)**

0.13

**Mounting Hole Diameter D (Metric)**

3.3 mm

**Mounting Hole Diameter D Max (Metric)**

3.3

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Flammability**

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**Certification/Specification WEB**

UL

**Package Quantity(Imperial)**

1000

**Package Quantity (Metric)**

1000

**Customs Number**

3926909987