

Specification Sheet

Part Number: T30RSF0M4



Arrowhead Push-Mount Cable Tie, 6.3"L, 30lb, 0.04"–0.09" Panel Thickness, PA66HS, Black, 1000/pkg

| | |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number | 126-00702 |
| Type | T30RSF(U) |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Push Mount design provides quick and easy mounting.• Push mount style creates low insertion and high extraction force.• Ties "clicks" into place upon final installation signaling installer insertion is complete. |
| Quantity Per | bag |
| Product Description | Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting. |
| Short Description | Arrowhead Push-Mount Cable Tie, 6.3"L, 30lb, 0.04"–0.09" Panel Thickness, PA66HS, Black, 1000/pkg |

Global Part Name

T30RSF(U)-PA66HS-BK

Minimum Tensile Strength (Imperial)

30.0

Minimum Tensile Strength (Metric)

135

Length L (Imperial)

6.3

Length L (Metric)

161.0

Fixation Method

Arrowhead

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.14

Width W (Metric)

3.6

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.6

Bundle Diameter Max (Imperial)

1.3

Bundle Diameter Max (Metric)

31.0

Thickness T (Imperial)

0.05

| | |
|------------------------------------------------|----------------------------------------|
| Thickness T (Metric) | 1.2 |
| Height H (Imperial) | .20 |
| Height H (Metric) | 5.70 |
| Panel Thickness Min(Imperial) | 0.035 |
| Panel Thickness Max(Imperial) | 0.094 |
| Panel Thickness Min (Metric) | 0.9 |
| Panel Thickness Max (Metric) | 2.4 |
| Mounting Hole Diameter D (Imperial) | 0.19 - 0.22 |
| Mounting Hole Diameter D (Metric) | 4.7 - 5.6 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.19 |
| Mounting Hole Diameter D Max (Imperial) | 0.22 |
| Mounting Hole Diameter D Max (Metric) | 5.6 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |

| | |
|----------------------------------------|-----------------|
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL-ZODZ2.E64139 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909987 |