

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C
	VOLTAGE	100 V AC	APPLICABLE CONNECTOR	DF19#-*P-1H(**) 
	CURRENT	AWG28: 1A AWG30: 0.9A AWG32: 0.8A	APPLICABLE CABLE	OUTER DIAMETER: 0.6 mm MAX
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	x	x
MARKING	CONFIRMED VISUALLY.		x	x
ELECTRIC CHARACTERISTICS				
INSULATION RESISTANCE	100 V DC.	500 MΩ MIN.	x	-
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	x	-
MECHANICAL CHARACTERISTICS				
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	x	-
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	x	-
ENVIRONMENTAL CHARACTERISTICS				
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→5 TO 35→+85 →5 TO 35 °C TIME 30→2 TO 3 → 30 →2 TO 3 min UNDER 5 CYCLES.	①INSULATION RESISTANCE: 500 MΩ MIN. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	x	-
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		x	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 1	DIS-H-007469	YK. YAMAGUCHI	TS. KUMAZAWA	13. 04. 02
REMARKS		APPROVED	KJ. KATAYOSE	05. 01. 05
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.		CHECKED	TY. OMA	05. 01. 05
Unless otherwise specified, refer to JIS C 5402.		DESIGNED	SZ. ONO	05. 01. 05
		DRAWN	SZ. ONO	05. 01. 05
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-162779-01	
	SPECIFICATION SHEET	PART NO.	DF19G-*S-1C (05)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL685-	 1/1