DRAWING MADE IN THIRD ANGLE PROJECTION

/home/us016926/DMTECmod

PART NUMBER	REV	FIRST USED
1385267-1	B	122500-1
1385267-2	B	565435-5





1. RECOMMENDED SPARE PARTS.
2. GREASE LIGHTLY.
3. GUARD MUST BE IN PLACE WHEN OPERATING APPLICATOR IN A BENCH MACHINE.
4. LUBRICATE DAILY USING NO. 20 MACHINE OIL.
5. ITEMS WITH QTY OF REF SPECIFIED (EXCEPT ITEMS 78 AND 79) ARE USED ON ITEM 32.
6. ITEM 78 USED WITH G TERMINATOR ONLY.
7. ADJUST ITEM 29 TO ACHIEVE PROPER BEND WHEN CHANGING WIRE SIZES.
8. CUT TO LOENGTH AT ASSEMBLY.

TERMINAL NAME: #6 STUD, SPADE

42318

AMP TERMINAL AMP CRIMP SPECS

PAD LTR	CRIMP HEIGHT	WIRE SIZE
A	.078 ±.002 [1.98 ±0.05mm]	16
B	.071 ±.002 [1.80 ±0.05mm]	18
C	.067 ±.002 [1.70 ±0.05mm]	20
D	NOT	USED

CRIMP	SIZE	TYPE	RANGE
WIRE	.090 [2.29mm]	F	20-16
INSUL	-	-	-

WIRE STRIP LENGTH	TERM APPL SPEC	FEED	APPL INSTRUCTION	SET UP GAGE	LAYOUT
.172-.203	114-2084	.620	408-8039	458638-1	L2535

-2	-1	U/M	DWG SIZE	PART NO	DESCRIPTION	ITEM NO
						129
2	2	-	C	5-354778-7	PIN, WIRE DISC (.2780)C	128
2	2	-	C	4-354778-9	PIN, WIRE DISC (.2740)B	127
2	2	-	C	3-354778-5	PIN, WIRE DISC (.2670)A	126
1	1	-	A	986950-1	WASHER, FLAT PRECISION	125
1	1	-	A	217238-1	GENERAL INSTRUCTION PACKAGE	124
1	1	-	-	4088039	EF APPL INST 408-8039	123
						122
						121
REF	REF	-	A	1-21030-7	PIN,DOWEL(ø.187×1.50)HSG	120
REF	REF	-	A	1-21030-1	PIN,DOWEL(ø.187×.50)LEVER	119
REF	REF	-	A	21045-3	RING,RET"C"(ø.187)FD PIN	118
REF	REF	-	A	5-21028-1	PIN,STD SPRING(ø.12)FD ADJ ROD	117
REF	REF	-	A	21899-4	WASHER,FLAT(ø5/16)SCR ADJ	116
						115
						114
						113
REF	REF	-	A	21024-5	WASHER,LOCK(NO.10)FD ROD GDE	112
						111
6	6	-	A	21024-4	WASHER,LOCK(NO.8)SHEAR BL	110
						109
2	2	-	A	21018-4	NUT,HEX(4-40)DRAG	108
REF	REF	-	A	21018-5	NUT,HEX(6-32)FD ADJ PL	107
						106
2	2	-	A	21022-2	NUT,HEX SL(8-32)DRAG STUD	105
						104
						103
2	2	-	A	2-21006-6	SCR,SKT SET(4-40×.62)DRAG	102
1	1	-	A	21009-2	SCR,SKT SET(1/4-20×.25)RAM	101
2	2	-	A	21017-2	SCR,DRIVE(#2×.19)ID PLATE	100
1	1	-	A	1-21002-7	SCR,BHC(6-32×.38)CAM	99
1	1	-	B	461264-1	PLATE, IDENTIFICATION	98
REF	REF	-	A	6-23715-5	SCR,PAN HD(6-32×1.50)FEED ADJ	97
						96
2	2	-	A	2-21002-2	SCR,BHC(8-32×.50)STRIPPER	95
REF	REF	-	A	2-21002-9	SCR,BHC(10-32×.75)HSG CAP	94
1	1	-	A	22733-8	SCR,BHC(8-32×.38 LW)ANVIL	93
4	4	-	A	3-21002-3	SCR,BHC(1/4-20×.50)ST GD PL	92
REF	REF	-	A	2-22733-8	SCR,BHC(1/4-20×.62)BASE PL	91
						90
						89
						88
2	2	-	A	2-21000-7	SCR,SHC(8-32×.50)SLUG BLADE	87
4	4	-	A	2-21000-5	SCR,SHC(8-32×.25)STRIP GUIDE	86
						85
REF	REF	-	A	3-21000-7	SCR,SHC(10-32×.75)FEED ROD GDE	84
						83
REF	REF	-	A	3-21000-6	SCR,SHC(10-32×.62)FEED ADJ PL	82
REF	REF	-	A	3-21000-4	SCR,SHC(10-32×.38)PIVOT BLOCK	81
2	2	-	A	3-21002-0	SCR,BHC(10-32×.88)SHEAR PL	80
REF	-	-	A	455745-1	GUARD, WINDOW	79
-	REF	-	A	679532-1	INSERT, GUARD	78
						77
						76
						75
						74
						73
REF	REF	-	A	458109-1	WASHER, FLAT (SPECIAL)	72
REF	REF	-	A	690517-1	SPACER	71

QTY REQD PER ASSY — PARTS LIST

-1	LEADMAKER & BENCH MODEL G	MECH POST FEED
-2	BENCH MODEL K	MECH POST FEED

-2	-1	U/M	DWG SIZE	PART NO	DESCRIPTION	ITEM NO
REF	REF	-	A	22594-8	NUT, HEX	70
REF	REF	-	B	240628-1	PLATE, ADJ	69
REF	REF	-	B	240626-1	SHAFT, PIVOT	68
REF	REF	-	B	240633-1	BUSHING	67
REF	REF	-	A	455680-1	LEVER, INTERMEDIATE	66
REF	REF	-	B	240629-1	BLOCK, PIVOT	65
REF	REF	-	A	240632-2	SCR, ADJ	64
REF	REF	-	B	240659-3	PIN, CAM ROLLER	63
REF	REF	-	B	240658-1	CAM, ROLLER	62
REF	REF	-	B	454398-1	ROD, FEED	61
						60
REF	REF	-	C	454220-1	CAP, RAM	59
REF	REF	-	D	453736-1	HOUSING	58
						57
						56
REF	REF	-	B	240624-1	PIN, FEED FINGER	55
REF	REF	-	B	691499-1	SPRING, FEED FINGER	54
REF	REF	-	B	240635-1	FINGER, FEED	53
REF	REF	-	B	240634-1	LEVER, TERMINAL	52
						51
						50
						49
1	-	-	B	690501-3	CAM, POST FEED 1 1/8 ST	48
-	1	-	B	690501-4	CAM, POST-FEED 1 5/8 ST	47
						46
1	1	-	A	690191-1	PLUG, NYLON	45
1	1	-	C	455674-2	RAM	44
1	1	-	A	690125-1	WASHER, LAMINATED	43
1	1	-	A	690124-4	WASHER, RAM	42
1	1	-	A	7-21002-9	BOLT, CRIMPER(5/16-24×1.00)	41
						40
						39
1	1	-	A	690223-2	SPACER, INSULATION DISC	38
1	1	-	D	354777-1	WIRE DISC, PLASTIC	37
1	1	-	A	22480-5	WASHER, SPRING	36
1	1	-	B	690212-1	POST, RAM	35
						34
						33
1	1	-	D	458980-1	APPLICATOR, BASIC (SUB ASSY)	32
						31
						30
1	1	-	B	690759-9	TOOL, FORMING	29
1	1	-	B	3-690451-2	SPACER, STRIPPER	28
1	1	-	A	240639-1	STRIPPER	27
REF	REF	-	C	455676-1	PLATE, BASE	26
2	2	-	A	22354-8	DRAG, STUD	25
1	1	-	B	455678-6	PLATE, STRIP GUIDE	24
						23
2	2	-	A	4-22281-1	SPRING, DRAG	22
						21
1	1	-	A	454177-1	DRAG, STOCK	20
1	1	-	B	1-458030-8	GUIDE, STRIP (REAR)	19
1	1	-	C	1-458031-8	GUIDE, STRIP (FRONT)	18
REF	REF	-	A	454178-1	GUIDE, FEED ROD	17
REF	REF	-	A	4-22284-9	SPRING, FEED RETURN	16
						15
1	1	-	B	2-240641-1	SPACER, SLUG BLADE	14
						13
1	1	-	B	690783-1	SPACER, PLATE	12
1	1	-	B	1-240644-1	PLATE, REAR SHEAR	11
2	2	-	C	240645-8	SPACER, SHEAR PLATE	10
1	1	-	B	690784-2	PLATE, FRONT SHEAR	9
1	1	-	D	5-240654-2	ANVIL	8
1	1	-	B	1-240651-2	BLADE, SLUG	7
						6
1	1	-	C	3-240641-4	SPACER, SLUG BLADE	5
						4
						3
						2
1	1	-	C	1-456406-2	CRIMPER, WIRE	1

QTY REQD PER ASSY — PARTS LIST

REVISION OF EACH ASSY NO (WHEN BLANK, USE DWG REVISION)

P	F	LTR	REVISION RECORD	APP	DATE
		B	ECN 0150-0389-03	TE	4-03
		A	REVISED	TB	05/01

DIMENSIONS IN INCHES. DO NOT SCALE PRINT.
TOLERANCES UNLESS OTHERWISE SPECIFIED:
2 PLC DEC ±-
3 PLC DEC ±-
4 PLC DEC ±-
ANGLES ± -
SURF TEXTURE: √
REMOVE BURRS, BREAK SHARP EDGES R.015 MAX

MATL - HT TR - FIN -

DR 23APR01 A.ANDERSON | APP 23APR01 T.ELBIN | CHK - | REL -

AMP Incorporated, Harrisburg, PA 17105-3608

NAME END FEED HDM APPLICATOR | MACHINE REF MINI APPL

SCALE - | D | DWG NO 1385267 | SHEET 1 OF 1 | REV B

CAGE CODE 00779 | CUSTOMER AND ASSEMBLY DRAWING | RESTRICTED TO —

THIS DRAWING IS A CONTROLLED DOCUMENT.
THIS DRAWING IS UNPUBLISHED. © COPYRIGHT 2001 BY AMP INCORPORATED. ALL RIGHTS RESERVED. RELEASED FOR PUBLICATION: 2001

LOC A | DIST 66