

| APPLICABLE STANDARD | | | | |
|---------------------|---------------------------------|----------------|---------------------------|---------------------------|
| RATING | OPERATING TEMPERATURE RANGE | -25°C TO +85°C | STORAGE TEMPERATURE RANGE | -25°C TO +60°C |
| | OPERATING&STORAGE HUMIDTY RANGE | 85%MAX | APPLICABLE CABLE | CABLE DIAMETER : φ8.3~9.3 |
| | VOLTAGE | | | |
| | CURRENT | | | |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------|-------------|--------------|----|----|
|------|-------------|--------------|----|----|

CONSTRUCTION

| | | | | |
|---------------------|---------------------------------------|-----------------------|---|---|
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | X | X |

| | | | | |
|--|--|--|--|--|
| | | | | |
|--|--|--|--|--|

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|-------|--------------------------|----------|---------|------|
|-------|--------------------------|----------|---------|------|

| | | | | |
|---|--------------|---------|--------------|------------|
| 1 | DIS-E-003060 | TM. ONO | KN. ICHIKAWA | 09. 12. 14 |
|---|--------------|---------|--------------|------------|

| | | | |
|---|----------|---------------|------------|
| REMARK △ THIS PRODUCT SHALL BE MATED WITH DH3 * B-37S, IT APPLIES TO DH3 * B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402. | APPROVED | KN. ICHIKAWA | 09. 11. 17 |
| | CHECKED | KN. ICHIKAWA | 09. 11. 17 |
| | DESIGNED | MO. SHIMOYAMA | 09. 11. 17 |
| | DRAWN | TM. ONO | 09. 11. 16 |

| | | |
|--|-------------|----------------|
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | DRAWING NO. | ELC4-126588-00 |
|--|-------------|----------------|

| | | | | |
|------------|---------------------------|----------|-----------------|-------|
| HRS | SPECIFICATION SHEET | PART NO. | DH-37-CV1B | |
| | HIROSE ELECTRIC CO., LTD. | CODE NO. | CL244-0011-8-00 | △ 1/1 |