



- NOTES:** (b)
- MATERIAL: COPPER ALLOY
 - PLATING:
 - ITEM 1: SEE TABLE
 - ITEM 2: TIN PLATED
 - ITEM 3: NICKEL PLATED

Directive 2002/95/EC RoHS compliant

PLATING ITEM	PART-NO.
(b) GOLD FLASH over NICKEL	132A13009X
min. 30µin HARD GOLD over min. 50µin NICKEL	132C13009X

pos	qty	description	material	plating
3	1	RETAINING RING	COPPER ALLOY	NICKEL PLATED
2	1	MATING SIDE	COPPER ALLOY	see table
1	1	REAR SIDE	COPPER ALLOY	TIN PLATED

Stückliste

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	DO NOT ALTER CAD DRAWING BY HAND				tolerance ISO 2768-m	dim. in mm	scale: 5:1	material: SEE NOTES
					date	name	title: HIGH POWER CONTACT FEMALE SOLDER PIN 90° 15A D-SUB COMBINATION	
					drawn 11.01.13	Lehmenkühler		
					appd. 11.01.13	Mickenbecker		
					norm			
					d-old		dwg no: 13K1A1165	DIN-A4
2 x b	Ä4600	11.01.2013	K.H.	CONEC ®		part no: SEE TABLE	sh: 1	
a	Origin							
rev.	description	date	name					