

Media module - FL SFP FE WDM20-B - 2702438

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fast Ethernet SFP WDM module for transmission up to a maximum of 20 km on a single fiber with a wavelength of 1550/1310 nm.

Product Description

SFP WDM module with a data transmission speed of 100 Mbps, a wavelength of 1310/1550 nm, and a maximum transmission length of 20 km.



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 189147
GTIN	4055626189147

Technical data

Dimensions

Width	13.7 mm
Height	8.95 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C (non-condensing)

Function

Basic functions	SFP module as FO port
Status and diagnostic indicators	via a Factoryline device

Supply voltage

Supply voltage	3.3 V (via Factoryline switch)
Max. current consumption	300 mA
Current consumption	300 mA

General

Mounting type	Insert in SFP slot
---------------	--------------------

Media module - FL SFP FE WDM20-B - 2702438

Technical data

General

Type AX	Factoryline devices with SFP slot
Net weight	32.3 g
Housing material	Metal

Approvals


Approvals

Approvals


RINA / DNV GL / LR / BSH

Ex Approvals

Approval details

RINA		http://www.rina.org/en	ELE205816XG
------	---	---	-------------

DNV GL		http://exchange.dnv.com/tari/	TAA00000YV
--------	--	---	------------

LR		http://www.lr.org/en	17/20056
----	---	---	----------

BSH		http://www.bsh.de/de/index.jsp	Nr. 966
-----	--	---	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>