

156-00135

Article Number: 156-00135

Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .59" - .71", PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 156-00135

**Type** T50SVCOC15-18

**Color** Black (BK)

- Features and Benefits**
- Omega Clip can be turned 360 degrees allowing for orientation in any direction.
  - Design allows quick and easy installation by hand without the need for tools.
  - Multiple bundle diameters available for all different ranges of bundles.

**Product Description** Omega Clip Cable Ties provide the opportunity to attach a wire or hose to an existing bundle. Offering a full range of orientations, the wire/hose can be orientated in any direction in relations to the main harness. The Omega Clip design is ideally suited for easing the application process on the production floor by allowing for an easy one-step snap fit of the harness assembly to the wire or hose

**Fixation Method (FF)** Omega Clips

**Identification Plate Position** none

**Tie Closure** plastic pawl

**Short Description** Omega Clip Cable Tie, 6.0" Long, Attaches to Diameter .59" - .71", PA66HS, Black, 500/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 222 N

**Length L (Imperial)** 6.0 "

**Length L (Metric)** 155 mm

**Attaches to Diameter (Imperial)** 0.6 " - 0.71 "

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Bundle Diameter Min. (Imperial)** 0.08 "

**Bundle Diameter Min. (Metric)** 2.0 mm

**Bundle Diameter Max. (Imperial)** 1.4 "

**Bundle Diameter Max. (Metric)** 35.0 mm

**Diameter Min. (Imperial)** 0.59 "

**Diameter Max. (Imperial)** 0.71 "

**Thickness T (Imperial)** 0.05 "

**Attaches to Diameter (Metric)** 15.0 - 18.0

**Thickness T (Metric)** 1.35 mm

## Logistics and Packaging

**Quantity Per** bag  
**Package Quantity (Metric)** 500  
**Carton Quantity** 3000 Pieces  
**Weight (Metric)** 3.08 kg

---

## Material and Specifications

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)  
Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HIRHS  
PA66HS

**Flammability** UL94 HB

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS compliant (Article 4 - 1)** Yes