



(WIRE) SEZ. FILO mm²	(INS. DIA. STD) Ø ISOL. STD	(INS. DIA. REDUCED) Ø IS. RID. FASE 3
0.50	---	1.5-1.7
0.75	---	1.7-1.9
1.0	---	1.9-2.1
1.5	---	2.2-2.4

STAGNATO	OTTONE OT 70	282165-1
FINITURA / COLORE (FINISH / COLOUR)	MATERIALE (MATERIAL)	NUMERO (PART NUMBER)

CUSTOMER DWG. FOR REFERENCE ONLY DISEGNO PER CLIENTE SOLO PER RIFERIMENTO

THIS DRAWING IS UNPUBLISHED RELEASE FOR PUBLICATION 19
 © COPYRIGHT 1979 BY AMP INCORPORATED, HARRISBURG, PA. ALL INTERNATIONAL RIGHT RESERVED AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENT AND/OR PATENT PENDING

TOLLERANZE, SE NON DIVERSAMENTE SPECIFICATO (TOLERANCES, UNLESS OTHERWISE SPECIFIED)	DIAM. ISOLANTE (INS. DIA. RANGED) 1.5-2.4	RANGO FILO (WIRE RANGED) DIA 0.5-1.5 mm²	SCALA (SCALED) -
± 0.3	AMP ITALIA S.p.A. Corso F.lli Cervi, 15 COLLENO (TORINO)		
ANGOLI (ANGLES) ± 2°	DESCRIZIONE (DESCRIPTION) 6.3 SERIES FLAG POSITIVE LOCK RECEPTACLE		

DIS. VERGANO P. (DR.) 3 OCT. 90	LOC. SIZE NUMERO (DWG. NO.) A3 C-282165	REV. (REV.) C	FOLIO (SHEET) 1 DI (OF) 1
---------------------------------	---	---------------	---------------------------

REV. (REV.)	REVISIONI (REVISION RECORD)	DIS. DATA (DR. DATE)
-	ERA 90-51114	-
C	MODIFIED PER ET00-0225-98 P.B. 02/25/98	14/3
A	IN PRODUZIONE ECHI-2798	14/3

NOTE:
 1 DA MISURARSI CON LA MOLLA IN POSIZIONE ORIZZONTALE
 2 ADATTO PER TERMINALE MASCHIO CON FORO, SECONDO TABELLA FIAT 91319 FOGLIO 2 (TIPO A)

SENSO DI USCITA DALLA BOBINA