



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=± 0.4mm
X.XX=± 0.25mm
 3. CONTACT RATING: 50mA @ 12VDC
 4. CONTACT MATERIAL: SILVER
 - ▲ 5. OPERATING FORCE: 260± 50gf
 6. TRAVEL: 0.25 +0.2/-0.1mm
 7. CONTACT RESISTANCE: 100mΩ MAX.
 8. ELECTRICAL LIFE: 100,000 CYCLES
 9. PACKAGING: 1,000 PCS RADIAL
 10. 2002/95/EC (ROHS) COMPLIANT
 11. ▲ DENOTES CRITICAL PARAMETERS.

C	22306	DRAWING UPDATES	5/12/16	MJR
B	16884	UPDATE NOTES, .30 DIM TO .25	1/18/07	TN
A	15808	RELEASE FOR PRODUCTION	2/23/06	PH
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED



TITLE TL59NF260Q				
SCALE 2:1	DATE 2/23/2006	DR PH	DWG P010622	REV C