

## Crimp contact - IPCC 16- 4-MT - 1733385

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Single crimp pin contact for flexible cable with 4 mm<sup>2</sup> cross section.

### Product Features

- Simply snap into the VC-AR... panel cutout and you're done!
- No need for panel mounting flange
- Simply snap into the VC-AR... panel cutout and you're done!
- No need for panel mounting frame
- Crimp contacts are released using a flat-bladed screwdriver

### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
Weight per Piece (excluding packing)	1.8 g
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Electrical characteristics

Rated current	32 A
Maximum load current	32 A

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
---------------------------------	-------------------

#### Mechanical characteristics

Conductor cross section	4 mm <sup>2</sup>
Stripping length of the individual wire	8 mm
Insertion/withdrawal cycles	>= 25

#### General

Series	VC-D
--------	------

# Crimp contact - IPCC 16- 4-MT - 1733385

## Technical data

### General

Connection method	Crimp connection
-------------------	------------------

### Material data

Contact surface material	silver-plated
--------------------------	---------------

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC000796

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

---

Approvals

EAC / EAC / EAC

---

Ex Approvals

## Crimp contact - IPCC 16- 4-MT - 1733385

### Approvals

---

Approvals submitted

---

### Approval details

EAC
-----

EAC
-----

EAC
-----

---