

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
<b>SPECIFICATIONS</b>				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
<b>MECHANICAL CHARACTERISTICS</b>				
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES. <span style="border: 1px solid black; padding: 0 2px;">1</span>	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. <span style="border: 1px solid black; padding: 0 2px;">1</span>		X	-
<b>ENVIRONMENTAL CHARACTERISTICS</b>				
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.	X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
<span style="border: 1px solid black; padding: 0 2px;">1</span>				
REMARK		APPROVED	AO. SUZUKI	10.02.02
<span style="border: 1px solid black; padding: 0 2px;">1</span> EXAMINATION IS HELD WITH "DH60A- * * P".		CHECKED	KN. ICHIKAWA	10.02.01
		DESIGNED	TU. TANIGUCHI	10.02.01
		DRAWN	TU. TANIGUCHI	10.02.01
Unless otherwise specified, refer to JIS C 5402 .				
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126867-00	
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DH60A-SCREW	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0042-1-00	<span style="border: 1px solid black; padding: 0 2px;">1</span> / 1/1