



- Notes
- 1 One example of the rotation of ref. No. ⑥ to ref. No. ① is shown.
  - ② The recommended clamp torque of ref. No. ⑥ : 2 to 3 N·m.
  - ③ The recommended clamp torque of ref. No. ⑨ : 0.2 to 0.3 N·m.  
 LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑥ and ref. No. ⑧ from loosening.
  - 4 This products to be used with cable clamp RM21WTP-CP※(71)  
 ※ designate diameter of applicable cable.
  - 5 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure.  
 Please confirm before the use.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
5	BRASS	NICKEL PLATING	10	CHLOROPRENE RUBBER	(BLACK)
4	PPS	(BLACK) UL94V-0	9	BRASS	NICKEL PLATING
3	PPS	(BLACK) UL94V-0	8	PHOSPHOR BRONZE	NICKEL PLATING
2	COPPER ALLOY	SILVER PLATING 5 μm.	7	CHLOROPRENE RUBBER	(BLACK)
1	BRASS	NICKEL PLATING	6	BRASS	NICKEL PLATING

  

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△				
HIROSE ELECTRIC CO., LTD.			APPROVED : HY. KOBAYASHI 18.02.22 CHECKED : HY. KOBAYASHI 18.02.22 DESIGNED : HY. KISHI 18.02.22 DRAWN : MK. INOUE 18.02.08	DRAWING NO. EDC-110102-31-00 PART NO. RM21WTP-15S(31) CODE NO. CL109-1401-2-31		