



Wide Range Input Series-Regulated



MATING CONNECTORS AVAILABLE:

- Panel Mount Elpac P/N WMPNLB
- Board Mount Elpac P/N WMPCCA
- DC Output Connections - D5 - 5 Pin DIN

SINGLE OUTPUT			
MODEL	OUTPUT	MIN LOAD WATTS	MAX LOAD WATTS
WRI 2011-D5	+ 5V/4.0A	0	20
WRI 2012-D5	+ 12V/2.0A	0	24
WRI 3012-D5	+ 12V/2.5A	0	30
WRI 4212-D5	+ 12V/3.5A	0	42
WRI 3014-D5	+ 24V/1.25A	0	30
WRI 4214-D5	+ 24V/1.75A	0	42
WRI 4515-D5	+ 30V/1.5A	1.5	45
WRI 5215-D5	+ 30V/1.75A	8	52

OUTPUT PIN CONFIGURATION - 5 PIN DIN					
MODEL	PIN 1	PIN 2	PIN 3	PIN 4	PIN 5
WRI 2011	COM	+5V	+5V	COM	+5V
WRI 2012	COM	+12V	+12V	COM	+12V
WRI 2021	COM	+5V	+5V	COM	+12V
WRI 2721	COM	COM	+5V	COM	+12V
WRI 2731	COM	COM	+5V	-12V	+12V
WRI 3012	COM	COM	+12V	COM	+12V
WRI 3014	COM	COM	+24V	COM	+24V
WRI 3021	COM	COM	+5V	COM	+12V
WRI 3025	COM	N/C	+5V	COM	+5V
WRI 3031	COM	COM	+5V	-12V	+12V
WRI 4212	COM	COM	+12V	COM	+12V
WRI4214	COM	COM	+24V	COM	+24V
WRI 4221	COM	COM	+5V	COM	+12V
WRI 4231	COM	COM	+5V	-12V	+12V
WRI 4232	COM	COM	+5V	-12V	+12V
WRI 4515	COM	COM	+30V	COM	+30V
WRI 5215	COM	COM	+30V	COM	+30V

DUAL OUTPUT				
MODEL	OUTPUTS		MIN LOAD WATTS	MAX LOAD WATTS
	1	2		
WRI 3021-D5	+ 5V/2.0A	+ 12V/1.5/2.5A	0	30
WRI 3025-D5	+ 5V/3.0A	+ 5V/3.0A	8	30
WRI 2021-D5	+ 5V/3.0A	+ 12V/0.5A	0	20
WRI 4221-D5	+ 5V/3.0A	+ 12V/2.5/4.0A	0	42
WRI 2721-D5	+ 5V/4.0A	+ 12V/0.5A/1.5A	2	27

TRIPLE OUTPUT					
MODEL	OUTPUTS			MIN LOAD WATTS	MAX POWER WATTS
	1	2	3		
WRI 3031-D5	+ 5V/2.0A	+ 12V/1.5/2.5A	- 12V/0.5A	0	30
WRI 2731-D5	+ 5V/3.0A	+ 12V/0.5/1.5A	- 12V/0.5A	2	27
WRI 4231-D5	+ 5V/3.0A	+ 12V/2.5/4.0A	- 12V/0.5A	0	42
WRI 4232-D5	+ 5V/4.8A	+ 12V/1.5/2.5A	- 12V/0.5A	0	42

HOW TO ORDER

CALL {714} 476-6070 OR FAX {714} 476-6075
 ELPAC POWER SYSTEMS, 1562 REYNOLDS AVE., IRVINE, CA 92714-5612